

Product List - Acoustic - Pairs

ACOUSTIC PRODUCT RATINGS	Pairs - Active /Inactive		Ratings			Acoustic Gasket System					Vision System			Documentation		
	Product Type	Door Thickness	Product Code	Fire Listing	STC	Perimeter	Active Door, Door Bottom	Inactive Door, Door Bottom	Meeting Stile	Flush Bolt	Lite Kit	Glazing Size	Glazing Product	Test Reference	Gasket System Number	Vision System Number
ACOUSTIC PRODUCT RATINGS	RigiCore EX	1-3/4"	112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	-	-	-	C3867.03S-113-17	200	-
			112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	-	-	-	C3867.03S-113-17	201	-
			112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03S-113-17	200	300
			112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03S-113-17	201	300
			112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03S-113-17	200	300
			112000	-	44	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03S-113-17	201	300
	RigiCore GP	1-3/4"	110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	-	-	-	C3867.03T-113-17	200	-
			110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	-	-	-	C3867.03T-113-17	201	-
			110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03T-113-17	200	300
			110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03T-113-17	201	300
			110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03T-113-17	200	300
			110000 / 111000	20 min	43	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03T-113-17	201	300
	KB-40	1-3/4"	118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	-	-	-	C3867.03U-113-17	200	-
			118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	-	-	-	C3867.03U-113-17	201	-
			118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03U-113-17	200	300
			118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B2	Up to 216 in ²	11/16" Laminated (.060 PVB)	C3867.03U-113-17	201	300
			118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 1)	Pemko S773, Pemko 303 AS	Top Only	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03U-113-17	200	300
			118000 / 119000	20 min	39	Pemko S773 / S44	Pemko PDB 411 AE / ACP 112, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko PDB 411 AE / ACP 112, Pemko S773, 1/2" x 1/2" Polypile pad (Qty 2)	Pemko S773, Pemko 303 AS	Top, Bottom	MVP: Pemko LT-B3	Up to 216 in ²	7/8" Pyrostop	C3867.03U-113-17	201	300

Product List - Fire - Single Swing

FIRE LISTED PRODUCTS - SINGLE SWING	Single Swing	Listing			Hardware Listed							Vision System			Documentation
	Product Family	Product Code	Detail	Max. Size	Hinges	Locksets	Exit Devices	Closers	Door Bottoms	Viewer	Electric Raceway	Lite Kit	Glazing Size	Glazing Product	Test Reference
	RigiCore EX	112000 113000	Category B 20 min PP w/Hose	4/0 x 8/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct RigiCore EX
	RigiCore GP	110000 111000	Category B 20 min PP w/Hose	4/0 x 8/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct RigiCore GP
	KB-41	128000 129000	Category B 20 min PP w/Hose	4/0 x 8/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct KB-41
	KB-40	118000 119000	Category B 20 min PP w/Hose	4/0 x 8/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct KB-40
	KB-35	114000 115000	Category B 20 min PP w/Hose	4/0 x 8/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct KB-35

Product List - Fire - Pairs

FIRE LISTED PRODUCTS - PAIRS	Pairs	Listing			Hardware Listed							Vision System			Documentation
	Product Family	Product Code	Detail	Max. Size	Hinges	Locksets	Exit Devices	Closers	Door Bottoms	Viewer	Electric Raceway	Lite Kit	Glazing Size	Glazing Product	Test Reference
	RigiCore GP	110000 111000	Category B 20 min PP w/Hose	6/0 x 7/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct RigiCore GP
	KB-40	118000 119000	Category B 20 min PP w/Hose	6/0 x 7/0	Per NFPA 80	Cylindrical, Cylindrical Deadbolt, Mortise, Cardreader	Surface-Mounted Vertical Rod, Rim-Type	Surface-Mounted, Mortised	Surface-Mounted, Mortised	1 allowed, 1/2" Max. Dia.	1 allowed	Metal Frame	up to 1320 in2	Listed & Labeled 5/16" min. thickness	See ITS Spec-Direct KB-40